

Nu-Edge® SL

Cobalt Chromium Brackets



Wire Sequence Guidelines

1

ALIGNMENT

.014"

TPO® Original Reflex® Nickel Titanium Wire
TPO Reflex Heat-Activated Nickel Titanium Wire

.016"

TPO Original Reflex Nickel Titanium Wire
TPO Reflex Heat-Activated Nickel Titanium Wire

2

LEVELING

.016" x .022"

TPO Original Reflex Nickel Titanium Wire
TPO Reflex Heat-Activated Nickel Titanium Wire
TPO TiMolium® Titanium Wire

.018" x .025"

TPO Original Reflex Nickel Titanium Wire
TPO Reflex Heat-Activated Nickel Titanium Wire

.017" x .025"

TPO TiMolium Titanium Wire

3

WORKING PHASE

.016" x .022"

TPO Shiny Bright Stainless Steel Wire

.018" x .025"

TPO Shiny Bright Stainless Steel Wire

4

DETAILING FINISHING PHASE

.016" x .022"

TPO Shiny Bright Stainless Steel Wire

.018" x .025"

TPO Shiny Bright Stainless Steel Wire

FULL ENGAGEMENT OF SLOT

.017" x .025"

TPO Shiny Bright Stainless Steel Wire

.0215" x .025"

TPO Shiny Bright Stainless Steel Wire

Find out more at **tportho.com**
or call **+27 (0) 11 100 0956**

